




Effective solutions for windows manufacturers and fitters

Unit 4203 Oakfield Close, Tewkesbury Business Park, Tewkesbury, Glos GL20 8PF

T: 01684 290944

E: sales@gtwindowproducts.co.uk W: www.gtwindowproducts.co.uk

GT Securi-Clip



 \checkmark

۲۲

Use SB000 Base Plate with GT011 Pink Packer

Use same combination for all transoms and mullions with fixed glazed units. All fixings, where possible, should go into steel reinforcing.

All drawings are not to scale Reinforcement and fixings have been omitted for clarity UK Fasteners screws were used for testing when required **GT SECURI-CLIP** is a patented glass retention system which, when fitted in the appropriate numbers and position, assists internally and externally beaded windows and doors to meet the requirements of PAS 23/24. (see system test reports)

The clip set assembly is comprised of a baseplate, a clip to suit the sealed unit thickness and a buffer to prevent contact between glass and clip. A profile related packer is available to adapt the base when required for recessed profile.

GT SECURI-CLIP may be used on PVCu, Aluminum or Timber windows and doors.

Assembly into a window or door frame is quick and easy either for on site glazing or factory glazing, which ever suits your own requirements.

The operation of de-glazing is simplified by using a designated key.





Legend 70 (Internal)

٦ſ

חר